

SEWAGE DISPOSAL SYSTEM SEPARATION REQUIREMENTS

Include a scaled drawing or survey map showing the proposed location of the subsurface sewage disposal system, 100% sewage reserve area (12,500 square feet in subdivisions), driveway(s) and well(s) on this property. The sketch must also include locations of well(s) and septic(s) on adjacent properties.

NOT TO BE COMPLETED BY APPLICANT

Inspected by: _____ on _____ 20____

Accompanied by: _____

DESCRIPTION OF WORKS, SUCH AS NUMBER, NAME AND CAPACITY OF UNITS:

INSTALLATION OF:

- () _____ gallon septic tank
- () _____ water tight distribution box(es).
- () Title field with _____ lineal feet of pipe in 2 foot trenches placed _____ foot on center, with a minimum of 12' of #1 and #2 crushed stone to encompass soil pipe to the width of trench, with 6' of stone under pipe.
- () _____ run-of-bank gravel fill, with all laterals tied in, minimum of 3' of fill under laterals and 8' from center of outside laterals to edge of fill.
- () Minimum separation of 100; from well, 100; from any classified stream, spring, brook, marsh or any other body of water, 50' from any storm water swales and 15' from the property line.

INSPECTORS' COMMENTS

FOR USE BY THE ULSTER COUNTY DEPARTMENT OF HEALTH

It is the opinion of the Ulster County Department of Health that this Sewage Disposal System _____ expected to function satisfactorily and is _____ likely to create an unsanitary condition, with reasonable usage and proper maintenance.

DATE _____ SIGNATURE _____